



Spartech's PolyPrime™ line of products offers many unique brands for a variety of applications. Primo™ is a premium material offering superior ink receptivity, making it an ideal choice for numerous printed product applications. Our Primo™ plastic sheet is stronger and stiffer with better tensile strength. It is the perfect alternative to Rigid PVC with better performance characteristics and is environmentally friendly.

**BENEFITS**

- Lower cost & weight than Rigid PVC
- Offers superior ink receptivity
- Durable and stiffer with better tensile strength
- Excellent dimensional stability
- Strong resistance to environmental stress cracking
- Material die-cuts well
- Recyclable - #5 plastic

**APPLICATIONS**

- Indoor banners
- Signage
- Menus
- Packaging
- Point of Sale Displays
- Horticultural plant tags
- Tags



**Primo™ TYPICAL PHYSICAL PROPERTIES**

For detailed physical properties information on this branded product, please contact your sales representative or go to [spartech.com](http://spartech.com) to request materials.

**Primo™ SPECIFICATIONS**

Order Size	1000 lb min		
Appearance	White		
Gauge	0.010 - 0.060		
Opacity Range (based on 0.012G)	83-95% (using a contact opacity meter)		
Roll Stock	Web Width Min	12"	
	Web Width Max	48" (may vary based on gauge)	
Roll Diameter	Minimum	12"	
	Maximum	32"	
Core Size	6" core		
Sheet Stock	Width Min	12"	
	Width Max	50" (may vary based on gauge or finish)	
	Length Min	24"	
	Length Max	100"	
Surface Treat	Corona	2 sides	Greater than 45 dyne level
Surface Finish	PolyLux	Dull Smooth/Light Matte	

Call 800-428-0840 or email [sales@spartech.com](mailto:sales@spartech.com) to order these products.



1414 Crawford Drive, Crawfordsville, IN 47933 • 800-428-0840 • Fax: 800-955-0053 • [www.spartech.com](http://www.spartech.com)



Spartech is a U.S. based company.

Copyright ©2022, Spartech, LLC. Spartech makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Spartech makes no warranties or guarantees respecting suitability of either Spartech's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. SPARTECH MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or product reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.