

TerraCard™

Spartech's PolyPrime™ line of products offers many unique brands for a variety of applications.

BENEFITS

- UV Printable - Screen, Digital & Offset
- Lower price than styrene and polycarbonate
- Improved processing
- Strong resistance to environmental stress cracking
- Won't crack, break, become brittle or discolor
- Improved material stiffness (similar to styrene)
- Low minimum order size
- Custom sizes and thicknesses
- Natural mineral reducing fossil fuel content
- Recyclable plastic
- Lower cost and weight
- No Toxic/Hazardous Content
- Material Lay Flat



FEATURES & BENEFITS KEY

Improved Benefit over Styrene
Similar Characteristic to Styrene



TerraCard™ SPECIFICATIONS

Order Size	1000 lb min		
Appearance	White		
Gauge	0.012 - 0.060		
Opacity Range (based on 0.015G)	83 - 95%		
Roll Stock	Web Width Min	12"	
	Web Width Max	48" (may vary based on gauge)	
Roll Diameter	Minimum	12"	
	Maximum	32"	
Core Size	6" core		
Sheet Stock	Width Min	12"	
	Width Max	50" (may vary based on gauge or finish)	
	Length Min	24"	
	Length Max	100"	
Surface Treat	Corona	2 sides	Greater than 45 dyne level
Surface Finish	PolyLux	Dull Smooth	

TerraCard™ TYPICAL PHYSICAL PROPERTIES

For detailed physical properties information on this branded product, please contact your sales representative or go to spartech.com to request materials.

Call 800-428-0840 or email sales@spartech.com to order these products.



1414 Crawford Drive, Crawfordsville, IN 47933 • 800-428-0840 • Fax: 800-955-0053 • www.spartech.com



Spartech is a U.S. based company.