

Royalite® WC

High Impact Rigid PVC Film

Product Description

Royalite WC is a high impact rigid backer film for medium to heavy-duty wallcovering and clean room applications.

- Available in various roll lengths depending on gauge
- Consistent physical properties
- Anti-Flame/Smoke material
- Available from 0.006" to 0.012" thick
- Available in custom widths from 25" to 65"
- Suggested Packaging .375/.500 wall cardboard cores, 800 yards/roll, pyramid roll configuration
- Shelf Life - 3 months. Product processed within 3 months, preferably 1 month.

Technical Properties

Property	Test Method	Value
Shrinkage	ASTM D-1204	-8% max
Multiaxial Impact	ASTM D-3763	1.7 ft lbs
Tensile Strength MD 20"/min with 5" jaw	ASTM D-638	4,500 psi, <50% elongation
Tensile Strength CD 20"/min with 5" jaw	ASTM D-638	3,500 psi, <50% elongation
Gauge	Dead weight micrometer	+/- 5% target
Width		+¼" - 0
Color		Visual to standard DE, DL, Da and Db upon request
Phthalate Content	CPSIA accredited testing (3 rd party)	Available upon request

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**