

SurfaceChoice™ Realtree Xtra® Korad® over ABS

Product Description

The Realtree Xtra®Korad® capped ABS combines the toughness of high impact ABS with the weather resistant features of Korad® film, which is laminated to the prime surface of the sheet. Korad® Capped ABS provides high impact strength, and UV resistance, yielding a value engineered weatherable sheet product.

Technical Properties

Property	Test Method	Value
Specific Gravity (color dependent)	ASTM D-792	1.04
Izod Impact (Notched) 73°F	ASTM D-256	7.0 ft-lbs/in
Tensile Strength	ASTM D-638	5,500 psi
Flexural Strength	ASTM D-790	8,000 psi
Flexural Modulus	ASTM D-790	255,000 psi

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**